

LINKSYS®

A Division of Cisco Systems, Inc.

Telephone service through your Wireless-G Internet connection!



The Linksys Wireless-G IP Phone enables high-quality telephone service through a Wireless-G network and high-speed Internet connection. Connect at home, your office, or at a public hotspot, and make phone calls through your low-cost Voice over IP service.

You can also surf the Internet with the built-in web browser and backlit full-color screen. The handset features peer-to-peer dialing, speed dial, conference calling, call waiting, transfer, and forwarding, mute, hold and selectable ring tones.

Get the value of low-cost VoIP service with the convenience of Wireless-G connectivity with the Wireless-G IP Phone from Linksys.

Make low-cost calls
from wireless hotspots

Built-in web browser

Full-featured handset

Wireless-G IP Phone

VoIP
Voice

Product Data

Model No. **WIP330-NA**

CISCO SYSTEMS


Wireless-G IP Phone

Features

- Support SIP v2 Standards
- Compliance with IEEE 802.11b/g Wireless Standard
- Powered by Microsoft Windows CE, with IE Web browser
- High Resolution Color LCD Screen
- Support QoS (Quality of Service) to Ensure Best Quality Voice
- Enhanced Power Saving Design for Extended Standby and Talk Time
- 35 hours Standby Time, 3 hours Talk Time
- High Hot Spot Connectivity with Fast Authentication
- Supports Auto-Provisioning using HTTP or HTTPS for Configuration and Upgrades

Specifications

Model	WIP330-NA
Standards	802.11b, 802.11g
Channels	11 Channels (US, Canada)
Transmit Power	12 dBm for 802.11b/g @ Normal Temp Range
External Interface	One Mini USB 1.1 Port, One Stereo Ear Phone Jack
Display	QVGA TIF 2.2 inch LCD with 65K Colors
Network Protocols	TCP/IP, IPV4
Security	WEP (64/128), WPA-PSK Encryption
QoS	ToS
Voice Protocols	SIP v2 Session Initiation Protocol (RFC3261), SDP (RFC2327)
Voice Codecs	G.711(A-law and mu-law), G.729 A/B
DTMF Transmission	In-band, Out-band (RFC2833)
Voice Quality	Acoustic Echo Cancellation Jitter Buffer Control Comfortable Noise Generation Packet Loss Concealment

Environmental

Dimensions (W x H x D)	1.84" x 5.32" x 0.74" (46.7 mm x 135.2 mm x 18.8 mm)
Unit Weight	4.20 oz. (0.12 kg)
Power	3.7V 1250mAh Lithium Battery, 5V 1.0A AC Adapter
Certifications	FCC, cUL, CE
Operating Temp.	32°F to 113°F (0°C to 45°C)
Storage Temp.	-4°F to 131°F (-20°C to 55°C)
Operating Humidity	10% to 85% Relative Humidity, Non-Condensing
Storage Humidity	10% to 95% Non-Condensing

Linksys
A Division of Cisco Systems, Inc.
18582 Teller Avenue
Irvine, CA 92612 USA

E-mail: sales@linksys.com
support@linksys.com

Web: <http://www.linksys.com>

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our Worldwide Web Site at www.linksys.com.

Minimum Requirements

- Internet Connection (cable/DSL/other)
- Wireless Router / Access Point with DHCP Server
- Activated VoIP Service

Package Contents

- Handset
- Power Adapter
- Quick Installation
- User Guide on CD-ROM

Check the product package and contents for specific features supported. Specifications are subject to change without notice. Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2005 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.